

HQ-0222

Shipped in packet-tape reel(4,000pcs per reel)

Notice : It is requested to read and accept "IMPORTANT NOTICE" written on the back of the front cover of this catalogue.

●Absolute Maximum Ratings

Item	Symbol	Limit	Unit
Max. Input Voltage	V_C	6	V
Max. Input Current	I_C	17	mA
Operating Temp. Range	Topr.	-40 ~ +125	°C
Storage Temp. Range	Tstg.	-40 ~ +150	°C

※1:パッケージ内の各個の素子毎の値です。

●Electrical Characteristics($T_a=25^\circ\text{C}$)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Hall Voltage	$V_{H(i)}$ ^{※2}	B=50mT, $V_C=3\text{V}$	90		130	mV
Relative Output Voltage Ratio	V_{Hr} ^{※3}	B=50mT, $V_C=3\text{V}$	95		105	%
Input Resistance	R_{in}	B=0mT, $I_C=0.1\text{mA}$	370		570	Ω
Output Resistance	$R_{out(i)}$	B=0mT, $I_C=0.1\text{mA}$	750		1150	Ω
Relative Resistance Ratio	R_{outr} ^{※4}	B=0mT, $I_C=0.1\text{mA}$	95		105	%
Offset Voltage	$V_{OS}(V_U)$	B=0mT, $V_C=3\text{V}$	-6		+6	mV
Temp. Coefficient of V_H	αV_H ^{※5}	B=50mT, $V_C=3\text{V}$ $T_a=25\sim 125^\circ\text{C}$		-0.2		%/°C
Temp. Coefficient of R_{in}	αR ^{※6}	B=0mT, $I_C=0.1\text{mA}$ $T_a=25\sim 125^\circ\text{C}$		-0.2		%/°C

※2. $V_H = V_{HM} - V_{OS}(V_U)$ (V_{HM} :meter indication)

※3. $V_{H(i)}$ ($i=1,2$) is Hall output voltage of 2-Hall Elements of one package.

$$V_{Hr \min} = \min(V_{H(i)})/V_{Havg} \times 100, V_{Hr \max} = \max(V_{H(i)})/V_{Havg} \times 100$$

$$\text{Where } V_{Havg} = (V_{H(1)} + V_{H(2)})/2$$

※4. $R_{out(i)}$ ($i=1,2$) is output resistance of 2-Hall Elements of one package.


$$R_{outr \min} = \min(R_{out(i)})/R_{out \text{ avg}} \times 100, R_{outr \ max} = \max(R_{out(i)})/R_{out \text{ avg}} \times 100$$

$$R_{out \text{ avg}} = (R_{out(1)} + R_{out(2)})/2$$


$$\text{※5. } \alpha V_H = \frac{1}{V_H(T_1)} \times \frac{V_H(T_2) - V_H(T_1)}{(T_2 - T_1)} \times 100$$

$$\text{※6. } \alpha R = \frac{1}{R(T_1)} \times \frac{R(T_2) - R(T_1)}{(T_2 - T_1)} \times 100$$


$$T_1 = 25^\circ\text{C}, T_2 = 125^\circ\text{C}$$




●Input Voltage Derating Curve



●Input Current Derating Curve



●Pinning




•Please be aware that our products are not intended for use in life support equipment, devices, or systems. Use of our products in such applications requires the advance written approval of our sales staff.
 Certain applications using semiconductor devices may involve potential risks of personal injury, property damage, or loss of life. In order to minimize these risks, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards. Inclusion of our products in such applications is understood to be fully at the risk of the customer using our devices or systems.


•Handling precautions required for preventing electrostatic discharge.

•This product contains gallium arsenide (GaAs) .Handling and discarding precautions required.





●Dimensional Drawing (Unit : mm)



●Land pattern (for reference only) (Unit : mm)



●Characteristic Curves



※Magnetic Flux Density
 1 [mT]=10 [G]

in This Example: $R_{in}=425$ [Ω]、 $V_{os}=0.8$ [mV] [$V_c=3$ (V)]