


# EQ-711L

Shipped in bulk(500pcs/Pack)

EQ-711L is composed of an InAs Quantum Well Hall Element and a signal processing IC chip in a package  
 Notice:It is requested to read and accept "IMPORTANT NOTICE" written on the back of the front cover of this catalogue.

## ●Operational Characteristics




## ●Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limit	Unit
Supply Voltage	V <sub>CC</sub>	6	V
Output Current	I <sub>out</sub>	±1.2 <sup>(*)</sup>	mA
Operating Temperature Range	T <sub>opr</sub>	-30 ~ 100	°C
Storage Temperature Range	T <sub>stg</sub>	-40 ~ 125	°C

(\*) V<sub>CC</sub>=5V

## ●Functional Block Diagram



## ●Magnetic and Electrical Characteristics (Ta=25°C Vcc=5V)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Supply Voltage	V <sub>CC</sub>		3	5	5.5	V
Supply Current	I <sub>CC</sub>			9	12	mA
Offset Voltage	V <sub>out0</sub>		2.35	2.5	2.65	V
Magnetic Sensitivity	V <sub>H</sub>	B=25mT	50	65	80	mV/mT
Output Saturation Voltage 1 <sup>(*)</sup>	V <sub>satH</sub>	I <sub>out</sub> =-0.5mA	V <sub>CC</sub> -0.3		V <sub>CC</sub>	V
Output Saturation Voltage 2 <sup>(*)</sup>	V <sub>satL</sub>	I <sub>out</sub> =0.5mA	0		0.3	V
Output Bandwidth <sup>(*)</sup>	f <sub>T</sub>	10% decrease frequency		100		kHz
Response Time <sup>(*)</sup>	T <sub>r</sub>	90% arrival		3	5	μsec
Temp. coefficient of V <sub>H</sub> <sup>(**)</sup>	αV <sub>H</sub>	The maximum error from room temperature	-5	0	5	%
Temp. coefficient of V <sub>out0</sub> <sup>(**)</sup>	αV <sub>out0</sub>	Ta=-30~100°C least squares approximation	-0.5	0	0.5	mV/°C


(\*) : design targets

1 [mT]=10 [Gauss]

(\*\*) : for reference only


- Please be aware that our products are not intended for use in life support equipment, devices, or systems. Use of our products in such applications requires the advance written approval of our sales staff.  
Certain applications using semiconductor devices may involve potential risks of personal injury, property damage, or loss of life. In order to minimize these risks, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards. Inclusion of our products in such
- This product contains gallium arsenide(GaAs).Handling and discarding precautions required.

●Package (Unit:mm)




※The sensor senter is located within the  $\phi 0.3\text{mm}$  circle.


●Supply Voltage




●Operational Characteristics



●Temperature dependence of VH



●(For reference only) Temperature dependence of Vout0



## IMPORTANT NOTICE

- These products and their specifications are subject to change without notice. When you consider any use or application of these products, please make inquiries the sales office of Asahi Kasei EMD Corporation (AKEMD) or authorized distributors as to current status of the products.
- AKEMD assumes no liability for infringement of any patent, intellectual property, or other rights in the application or use of any information contained herein.
- Any export of these products, or devices or systems containing them, may require an export license or other official approval under the law and regulations of the country of export pertaining to customs and tariffs, currency exchange, or strategic materials.
- AKEMD products are neither intended nor authorized for use as critical components<sup>Note1)</sup> in any safety, life support, or other hazard related device or system<sup>Note2)</sup>, and AKEMD assumes no responsibility for such use, except for the use approved with the express written consent by AKEMD. As used here:
  - Note1) A critical component is one whose failure to function or perform may reasonably be expected to result, whether directly or indirectly, in the loss of the safety or effectiveness of the device or system containing it, and which must therefore meet very high standards of performance and reliability.
  - Note2) A hazard related device or system is one designed or intended for life support or maintenance of safety or for applications in medicine, aerospace, nuclear energy, or other fields, in which its failure to function or perform may reasonably be expected to result in loss of life or in significant injury or damage to person or property.
- It is the responsibility of the buyer or distributor of AKEMD products, who distributes, disposes of, or otherwise places the product with a third party, to notify such third party in advance of the above content and conditions, and the buyer or distributor agrees to assume any and all responsibility and liability for and hold AKEMD harmless from any and all claims arising from the use of said product in the absence of such notification.

## ASAHI KASEI EMD CORPORATION

### Headquarters

1-23-7 Nishi-Shinjyuku, Shinjyuku-ku, Tokyo 160-0023, Japan  
TEL : +81-3-6911-2800 FAX : +81-3-6911-2815

### Osaka Office

1-2-6 Dojimahama Kita-ku, Osaka 530-8205, Japan  
TEL. +81-6-6347-3133 FAX. +81-3-6911-2815

### Europe Office

Market House, 19/21 Market Place, Wokingham, Berkshire, RG40 1AP, U.K.  
TEL : +44-118-979-5777 FAX : +44-118-979-7885

### Shanghai Office

Room 2321, Shanghai Central Plaza, 381 Huaihai Zhong Road, Shanghai 200020, China  
TEL. +86-21-6391-6111 FAX. +86-21-6391-6686

### Seoul Office

8th fl., KTP B/D, 27-2 Yoido-dong, Youngdungpo-gu, Seoul 150-742, Korea  
TEL. +82-2-3775-0990 FAX. +82-2-3775-1991

## AKM Semiconductor, Inc

### Western US Sales

1731 Technology Dr Suite 500 San Jose, CA 95110, USA  
TEL. +1-408-436-8580 FAX. +1-408-436-7591

### Eastern US Sales

629 Bamford Road Cherry Hill, NJ 08003, USA  
TEL. +1-856-424-7211 FAX. +1-856-424-7344

### URL

<http://www.akemd.com>

## North American Distributor: GMW Associates

955 Industrial Rd, San Carlos, CA 94070, USA  
TEL. +1-650-802-8292 FAX. +1-650-802-8298  
EMAIL [sales@gmw.com](mailto:sales@gmw.com) WEB [www.gmw.com](http://www.gmw.com)