



# Spacemag-Lite<sup>®</sup>

Three-Axis Magnetometer






## Spacemag-Lite® Three-Axis Magnetometer

Bartington Instruments offers a fluxgate magnetometer for spaceflight applications.

Spacemag-Lite® is ideal for a variety of low Earth orbit (LEO) missions, including commercial and scientific missions, where cost is a consideration.

The standard sensor is designed for CubeSat integration, though other configurations are also available depending on the mission requirement.



Bartington is a registered trade mark of Bartington Holdings Limited in the following territories: Argentina, Australia, Brazil, Canada, Chile, China, European Union, Hong Kong, Iceland, India, Israel, Japan, Malaysia, Mexico, New Zealand, Norway, Russia, Singapore, South Africa, South Korea, Switzerland, Taiwan, Turkey, United Kingdom, United States of America, and Vietnam.

Spacemag-Lite is a registered trade mark of Bartington Holdings Limited in the following territories: European Union, and United Kingdom.

Spacemag-Lite is used under licence by Bartington Instruments Limited.

## Spacemag-Lite<sup>®</sup> Specifications

Performance	
Number of axes	Three (right hand XYZ coordinate system)
Polarity	+ve non-inverting output when pointing North
Full-scale measuring range	$\pm 60\mu\text{T}$
Measurement noise floor	$>10$ to $\leq 50\text{pTrms}/\sqrt{\text{Hz}}$ at 1Hz
Offset error	$\pm 100\text{nT}$ (max) at 25°C
Scaling temperature coefficient	$\pm 100\text{ppm}/^\circ\text{C}$
Calibration error	$\pm 0.5\%$
Orthogonality error	$< 0.5^\circ$
Frequency response	$< 5\%$ amplitude error DC to 100Hz
Frequency range to -3dB	DC-1kHz minimum within -3dB level
Hysteresis	$< 0.1\%$ range for exposure to up to 10x range when unpowered
Excitation breakthrough	$< 20\text{mV}$ pk-pk at 16kHz
Start-up/settling time	99% of final value in 0.5s





## Spacemag-Lite® Three-Axis Magnetometer

Environmental	
Operating temperature - continuous	-40°C to +65°C
Operating temperature - intermittent	-40°C to +85°C
Storage temperature	-40°C to +85°C
EMC approvals	BS EN61326
Thermal vacuum testing <sup>1</sup>	<10-5mbar -30°C to +60°C
Conformal coating	None

<sup>1</sup> Thermal Vacuum Testing carried out on one validation model. Thermal Vacuum Testing is not performed on each unit manufactured.

Mechanical	
Construction	Un-packaged PCB with PCB-mounted Probe or Harnessed Probe
Harness length	Up to 2 metres
Construction materials	All materials achieve $\leq 1\%$ TML and $\leq 0.1\%$ CVCM
Dimensions - probe	20mm x 20mm x 20mm
Dimensions - electronics	90.2mm x 95.9mm (CubeSat 810-00253 rev A5, PC-104)
Weight - SpaceMag-Lite	67g
Weight - SpaceMag-Lite (harness variant)	94g
Weight - SpaceMag-Lite Probe	42g
Mounting arrangement	See DR3777 Outline Drawing

Electrical	
Voltage input	5V and 3.3V
Current consumption - positive	33.5mA zero field; 35mA in full range field (5V) and 8.5mA (3.3V)
Analogue output	Balanced differential output
Output impedance	1.5 $\Omega$



The specifications of the products described in this brochure are subject to change without prior notice.

Bartington Instruments Ltd  
5, 8, 10, 11 & 12 Thorney Leys Business Park  
Witney, Oxford OX28 4GE. England

**Telephone:** +44 (0)1993 706565  
**Email:** sales@bartington.com

 **Bartington**<sup>®</sup>  
Instruments